

MICHELIN INFLATION CHARTS FOR LIGHT TRUCK TIRES

To select the proper load and inflation table, locate your tire size in the following pages, then match your tire's sidewall markings to the table with the same sidewall markings. If your tire's sidewall markings do not match any table listed, please contact your MICHELIN® dealer for the applicable load and inflation table.

Industry load and inflation standards are in a constant state of change, and Michelin continually updates its product information to reflect these changes. Printed material may not reflect the latest load and inflation standards.

NOTE: Never exceed the wheel manufacturer's maximum pressure limitation.

S = Single configuration, or 2 tires per axle.

D = Dual configuration, or 4 tires per axle.

Loads are indicated per axle.

WHEEL DIAMETER 16"	PSI	35	40	45	50	55	60	65	70	75	80	MAX LOAD & PRESSURE ON SIDEWALL
	kPa	250	280	310	350	380	410	450	480	520	550	
LT215/85R16 LRE LTX A/T2, LTX M/S2, XPS RIB, XPS TRACTION	LBS SINGLE	2990	3280	3570	3880	4100	4360	4670	4860	5100	5360	S 2680 LBS AT 80 PSI
	LBS DUAL	5440	5960	6500	7060	7460	7940	8600	8840	9280	9880	D 2470 LBS AT 80 PSI
	KG SINGLE	1990	1488	1619	1760	1860	1978	2120	2205	2313	2430	S 1215 KG AT 550 KPA
	KG DUAL	2520	2703	2948	3200	3384	3602	3900	4010	4209	4480	D 1120 KG AT 550 KPA
LT225/75R16 LRE LTX A/T2, LTX M/S, XPS RIB	LBS SINGLE	3000	3300	3580	3880	4120	4380	4670	4880	5120	5360	S 2680 LBS AT 80 PSI
	LBS DUAL	5460	6000	6520	7060	7500	7980	8600	8880	9320	9880	D 2470 LBS AT 80 PSI
	KG SINGLE	1400	1500	1625	1760	1870	1990	2120	2215	2320	2430	S 1215 KG AT 550 KPA
	KG DUAL	2540	2720	2960	3200	3400	3620	3900	4030	4230	4480	D 1120 KG AT 550 KPA
LT235/85R16 LRE LTX A/T2, LTX M/S2, XPS RIB, XPS TRACTION	LBS SINGLE	3400	3740	4060	4410	4670	4970	5246	5530	5810	6084	S 3042 LBS AT 80 PSI
	LBS DUAL	6180	6800	7380	8024	8500	9040	9524	10060	10580	11112	D 2778 LBS AT 80 PSI
	KG SINGLE	1580	1696	1842	2000	2118	2254	2380	2508	2635	2760	S 1380 KG AT 550 KPA
	KG DUAL	2880	3084	3348	3640	3856	4100	4320	4563	4799	5040	D 1260 KG AT 550 KPA
LT245/75R16 LRE LTX A/T2, LTX M/S, XPS RIB	LBS SINGLE	3400	3730	4060	4410	4670	4960	5250	5530	5800	6084	S 3042 LBS AT 80 PSI
	LBS DUAL	6180	6780	7380	8024	8500	9020	9525	10060	10560	11112	D 2778 LBS AT 80 PSI
	KG SINGLE	1580	1690	1840	2000	2120	2250	2380	2510	2630	2760	S 1380 KG AT 550 KPA
	KG DUAL	2880	33075	3350	3640	3855	4090	4320	4560	4790	5040	D 1260 KG AT 550 KPA
LT265/75R16 LRE LTX A/T2, LTX M/S2	LBS SINGLE	3820	4200	4560	4940	5250	5580	6000	6210	6520	6830	S 3415 LBS AT 80 PSI
	LBS DUAL	6960	7640	8300	9080	9560	10160	11020	11300	11860	12340	D 3085 LBS AT 80 PSI
	KG SINGLE	1780	1905	2070	2240	2380	2530	2720	2815	2960	3100	S 1550 KG AT 550 KPA
	KG DUAL	3240	3465	3765	4120	4340	4610	5000	5125	5380	5600	D 1400 KG AT 550 KPA

WHEEL DIAMETER 17"	PSI	35	40	45	50	55	60	65	70	75	80	MAX LOAD & PRESSURE ON SIDEWALL
	kPa	250	280	310	350	380	410	450	480	520	550	
LT235/80R17 LRE LTX M/S2	LBS SINGLE	3450	3790	4110	4540	4740	5030	5360	5610	5880	6170	S 3085 LBS AT 80 PSI
	LBS DUAL	6280	6900	7480	8160	8620	9160	9880	10220	10700	11340	D 2835 LBS AT 80 PSI
	KG SINGLE	1600	1720	1865	2060	2150	2281	2430	2545	2670	2800	S 1400 KG AT 550 KPA
	KG DUAL	2920	3130	3390	3700	3910	4155	4480	4635	4855	5140	D 1285 KG AT 550 KPA
LT245/70R17 LRE LTX A/S	LBS SINGLE	3380	3710	4020	4410	4630	4920	5200	5480	5750	6000	S 3000 LBS AT 80 PSI
	LBS DUAL	6160	6760	7320	7940	8420	8960	9340	9980	10460	11020	D 2755 LBS AT 80 PSI
	KG SINGLE	1570	1685	1825	2000	2100	2230	2360	2485	2610	2720	S 1360 KG AT 550 KPA
	KG DUAL	2860	3065	3320	3600	3820	4065	4240	4525	4745	5000	D 1250 KG AT 550 KPA
LT245/75R17 LRE LTX M/S2	LBS SINGLE	3540	3890	4220	4540	4860	5160	5510	5750	6040	6170	S 3195 LBS AT 80 PSI
	LBS DUAL	6440	7080	7680	8160	8840	9400	10140	10460	11000	11340	D 2910 LBS AT 80 PSI
	KG SINGLE	1650	1765	1915	2060	2205	2340	2500	2608	2740	2900	S 1450 KG AT 550 KPA
	KG DUAL	3000	3210	3485	3700	4010	4265	4600	4745	4990	5280	D 1320 KG AT 550 KPA
LT265/70R17 LRE LTX A/S, LTX M/S2	LBS SINGLE	3780	4150	4510	4940	5190	5520	5820	6010	6200	6390	S 3195 LBS AT 80 PSI
	LBS DUAL	6880	7560	8200	9080	9440	10040	10720	10940	11280	11640	D 2910 LBS AT 80 PSI
	KG SINGLE	1760	1880	2044	2240	2360	2500	2640	2730	2800	2900	S 1450 KG AT 550 KPA
	KG DUAL	3200	3440	3720	4120	4280	4560	4860	4960	5120	5280	D 1320 KG AT 550 KPA