


AIRSTREAM


ELECTRIC AC

LET DATE	P.O.R.	REVISION RECORD	BY
-	E-207	Production Release	MT
A	E-207	Production Release	MT
B	E-207	Production Release	MT

BREAKER LAYOUT



- STD. BREAKER LABEL
- 20AMP-REFER. & GFI RECEP.T'S
 - 20AMP-MICRO. RECEP.T.
 - 20AMP-DINETT. RECEP.T'S
 - 20AMP-A/C
 - 30AMP-MAIN



M-8 POWER CENTER
MAIN, 30 AMP. HACR BREAKER, 10-2 ROMEX W/GRD.

CIRCUIT 1, 20 AMP. HACR BREAKER, 12-2 ROMEX W/GRD.
A. AIR CONDITIONER
TOTAL 13.8 AMPS.

CIRCUIT 2, 20 AMP. HACR BREAKER, 12-2 ROMEX W/ GRD.
B. CONVERTER WIRED DIRECT
D. DINETTE RECEPT. (DUPEX)
E. DINETTE NIGHTSTAND RECEPT. (DUPEX)
TOTAL 11.0 AMPS.

CIRCUIT 3, 20 AMP. HACR BREAKER, 12-2 ROMEX W/ GRD.
F. MICROWAVE OVEN (SINGLE RECEPT)
TOTAL 12.0 AMPS.

CIRCUIT 4, 20 AMP. GFI/C BREAKER, 12-2 ROMEX W/ GRD.
G. REFER. RECEPT (SINGLE)
H. GALLEY RECEPT.
J. MAIN AREA TV RECEPT. (DUPEX)
K. OUTSIDE RECEPT.
TOTAL 8.7 AMPS.


NOTE:

SYM.	DRAWING#	DESCRIPTION
H0	511871	Tail & Clearance Ham.
H1	510907	Front Clearance Ham.
H2	512241	Curb Side Cellg Ham.
H3	512240	Road Side Cellg Ham.
H4	512240	Road Side Cellg Ham.

*1) THE HARNESS CHART ONLY
SHOWS THE BASE DRAWING
NUMBER WITHOUT REVISION.

TIME	DATE	SCALE	REV.
30A	03/07	110V LAYOUT USA	D
03/07	952889	952889	B

Airstream



SEE SHEET #1 FOR NOTES.




ITEM	PART NUMBER	DESCRIPTION	QTY	BY
TOLERANCES ±				
NOT ASSY				
12V, ELEC. MAIN SCHEM. 16, 17 & 22° SPURT				
TITLE				
SCALE	DATE	REVISED BY	REV.	
N.T.S.	02/15/07	95228532	D	A
APPROVED BY				
M				



FILE	DESCRIPTION	QTY
PART NUMBER		
TOLERANCES		DRAWN BY
1		MI
MKT ASSY		APPROVED BY
		
PART ISSUE: 17 & 22 - S&P ART SPRT		
TITLE: SCHEMATIC, BASIC A/V		
SCALE	DATE	REV.
N.T.S.	3/9/07	D
DESIGN NUMBER: 93288832		

Diagram illustrating the rear view of Configuration 1 of the M109C self-propelled howitzer. The diagram shows the rear profile of the vehicle with various components labeled:

- ROAD SIDE** (top right)
- CURB SIDE** (bottom right)
- 18-9** (top right rear)
- 18-10** (top right rear)
- 18-11** (top right rear)
- LRC U.S. UNIT** (top right rear)
- LRC CANADA UNIT** (top right rear)
- 18-8** (top right rear)
- 18-5** (top left rear)
- 18-6** (top left rear)
- 18-7** (top left rear)
- 18-14** (center rear)
- 18-13** (center rear)
- 18-15** (bottom left rear)
- 18-16** (bottom left rear)
- 18-17** (bottom left rear)
- LRC U.S. UNIT** (bottom left rear)
- LRC CANADA UNIT** (bottom left rear)
- CONFIGURATION 1** (center left)
- REAR VIEW** (center left)




G:/Data/PIC/500886.JPG

SHEET 1 OF 2

LET	DATE	E.C.N.	REVISION RECORD	BY
-	4/05	-	PRUD. REL	MI
A	6/06	E-00068	LED LIGHT UPDATE	MI
B	8/06	E-00068	UPDATED CALC. TABLE.	MI
C	3/07	E-00159	ADD CONFG.#4	MI
D	4/07	E-00159	ADD NOTE #7, & #8	MI
E	5/07	T-01624	UPDATE PLATE HOLDER PN#511407	MI/KK
F	10/07	T-00210	NEW LED TEARDROP LTS	MI
G	7/08	T-02177	NEW TAIL/CLEAR. HARN. REL.	MI
H	1/10	T-02574	NEW LED OVAL 6" TAIL LT	MI

NOTE:

- Ⓐ 1. A WIRE TO BE 105G. TEW. UL/C25A LISTED
- Ⓐ 2. GROUND WIRES (C/L 150) TO BE WHITE.
- Ⓐ 3. INSULATE TERMS, WITH ELEC. TAPE IF UNUSED TO PREVENT SHORING.
- Ⓐ 4. SEE DRAWING 511871--CURRENT FOR TAIL HARNESS, AND DRAWING 510907--CURRENT FOR FRONT HARNESS.
- Ⓐ 5. THE WHITE COMMON FOR CONFIGURATION #2 INCLUDES THE 54 WATTS FOR THE BACK-UP LIGHTS ON THE CLASSIC.
- Ⓐ 6. THE GREEN OVERSEA LOAD AND SIDE CLEARANCE/ MARKERS LIGHTS ARE INCLUDED IN CALCULATIONS.
- Ⓐ 7. REMOVE UNUSED TAIL LIGHT CONNECTORS FROM 511871 AND BUTT SPlice TO AVOID SHORTS.
- Ⓐ 8. SEE SHELL DRAWINGS FOR ACTUAL PHYSICAL DIMENSIONS.
- Ⓐ 9. THIS LIGHT ASSEMBLY IS NOT REQUIRED ON THE CLASSIC MODEL TRAILER LINE.



ITEM	PART NUMBER	DESCRIPTION	QTY	UNIT
TOLERANCES ± N/A		Airstream	DRAWN BY M.A.I.	
NEXT ASS'Y			APPROVED BY	
TITLE		PRODUCT LINE	TRAILER	
SCHEMATIC, 12VDC 7-WAY				
SCALE N/A	DATE 04/13/05	DRAWING NUMBER 952794S1		REV. B H

952794S2

LET DATE

E.C.N.

REVISION RECORD

BY

LOAD CHART IS SEPARATED BY CONFIGURATION. (SEE SHEET #1 FOR CONFIGURATION NUMBER) (F)

SEE SHEET #1 FOR REVISIONS

TAIL LIGHTS				TAIL LIGHTS				TAIL LIGHTS			
CONF.#	A/S	PNH	QTY	DESCRIPTION	WATTS (PER LT)	STOP LT	TAIL LT	A/S	PNH	QTY	DESCRIPTION
1	512425	4	4	TAIL LIGHT-LED OVAL 6"	5W	5W	5W	511407	1	1	LIC. PLATE HOLDER W/LT (C168)
2	511973	4	4	LIGHT-STOP/TAI/TURN LED TRL	10.5W	1W	1W	511294	1	1	LIC. PLATE LICENSE PLATE
3	511860-01	4	4	LIGHT-4" ROUND LED RED #115-0001	3.5W	0.5W	0.5W	511407	1	1	LIC. PLATE HOLDER W/LT (C168)
4	511860-01	2	2	LIGHT-4" ROUND LED RED #115-0001	3.5W	0.5W	0.5W	511407	1	1	LIC. PLATE HOLDER W/LT (C168)

SEE APPENDIX 1, MAIN ELEC. SCHEMATIC


CLEARANCE/MARKER LIGHTS

A/S	PNH	QTY	DESCRIPTION	WATTS SUB-TOTAL
512226	4	4	MARKERLIGHT-AMBER TEARDROPLED	0.5W
512227	9	9	MARKERLIGHT-RED TEARDROPLED	2W
TOTAL CLR. LTS. WATTS = 6.5W				4.5W

7-WAY PARTLIST

ITEM	PART NUMBER	DESCRIPTION	QTY	U/M
1	512425	TAIL LIGHT-LED OVAL 6"	4	EA
2	511973	LIGHT-STOP/TAI/TURN LED TRL	4	EA
3	511860-01	LIGHT-4" ROUND LED RED #115-0001	4	EA
4	511860-01	LIGHT-4" ROUND LED RED #115-0001	2	EA
5	511407	LIC. PLATE HOLDER W/LT (C168)	1	EA
6	511294	LIC. PLATE LICENSE PLATE	1	EA
7	511407	LIC. PLATE HOLDER W/LT (C168)	1	EA

* = PRODUCTION USE MUST CURRENT HARNESS REVISION.



SEE SHEET #1 FOR NOTES

SHEET 2 OF 2

12VDC 7-WAY SCHEMATIC

Airstream

TRAILER

PRODUCT LINE

SCALE N/A

DATE 04/13/05

DRAWING NUMBER 952794S2

REV. B H



SEE SHEET #2 FOR OPTION WIRING. (OPTIONS MAY CHANGE THIS SHEET.)

CANADA (CSA) CHART

RECEIPT. LEGEND

- A. AIR CONDITIONER (CIR. 1)
- B. CONVERTER (PART OF M-8, DIRECT WIRED) (CIR. 2)
- C. MAIN AREA TV RECEIPT. (CIR. 4) (X)
- D. DINETTE RECEIPT. (CIR. 2)
- E. DINETTE NIGHTSTAND RECEIPT. (CIR. 2)
- F. MICROWAVE OVEN (SINGLE RECEIPT.) (CIR. 3)
- G. REEFER RECEIPT (SINGLE) (CIR. 4)
- H. GALLEY RECEIPT. (CIR. 4)
- J. BATH RECEIPT (CIR. 4)
- K. DUNSTON RECEIPT. (CIR. 4)

	WIRE, ROMEX #10-2 w/GROUND	CSA (ORG)	8FT
MAIN	WIRE, ROMEX #10-2 w/GROUND	510003	22FT
1	WIRE, ROMEX #12-2 w/GROUND	CSA (YEI)	510005
2	WIRE, ROMEX #14-2 w/GROUND	CSA (WHI)	510004
3	WIRE, ROMEX #14-2 w/GROUND	CSA (WHI)	510004
4	WIRE, ROMEX #14-2 w/GROUND	CSA (WHI)	510004
			50FT

SEE SHEET #2 FOR OPTION WIRING. (OPTIONS MAY CHANGE THIS SHEET.)

[illegible]

NOTE: GRID MARKS ARE 6" APART AND FOR REFERENCE ONLY.

120V. LOCATION CHART

FILE	PART NUMBER	DESCRIPTION	QTY	U
TECHNICALS				
2				
MKT ASSY				
PART NUMBER		22- SATARI SPORT		
TITLE		110V LBC/ROUT		
SCALE	DATE	DESIGN NUMBER		
M.T.S.	3/30/07	952893		
D	REV			

510907-02

No.	Ga.	Color	Cutting Length	Function
18	14	GREEN	256'	TAIL & CLR. L.T.
14	14	WHITE	268'	GROUND

WEIGHT: .90 LBS.

H1
TO
INTERIOR BODY
HARNESS

R.S. SIDE
MARKER LT.
18-1

18-2
R.S.
CLEARANCE LT.

18-3
C.S.
CLEARANCE LT.

18-4
C.S. SIDE
MARKER LT.

LET	DATE	ECN	REVISION RECORD	BY
A	5-90	4265	Production Release	J.S.
B	11-90	4282A	90 Was 70, 20 Was 12	J.S.
C	4/93	4409H	Added Butt Connectors	RA
D	6/93	4409S	Rev. For 1994 A/S Trl.	RA
E	12/00	4826B	Delete 3 Breakouts	RA
F	10/02	4947	Rev. To Add C.S. & R.S. Side Marker Lights, 80' Was 76'	RA
G	11/02	4947	11' WAS 4' RS/CS CLEARANCE ONLY	BS

OBSOLETE


ECA No.: T-02573
Name: MI
Date: 3/10
Replaced By: 510907-03
Disposition: *

- = 20 Ga. Wire □ = 14 Ga. Wire
○ = 18 Ga. Wire □ = 12 Ga. Wire
◇ = 16 Ga. Wire ◇ = 10 Ga. Wire
△ = 8 Ga. Wire

NOTE:
1) WIRE SHALL BE TEV 105°C UL & CSA
2) HARNESS SHALL CONFORM TO 951066 SPEC.
LIGHT PLACEMENT PER CONFIGURATION.

Terminals
Butt 100 Male
Butt 100 Female
Butt Connector
Ring Hardware
Spade 250 Female
Spade 250 Male

ITEM	PART NUMBER	DESCRIPTION	QTY	UOM
4	500419	TERMINAL, #10 RING, 14-16 GA.	1	EA
3	510537-08	WIRE, 14 GA., 19 STRAND, GREEN	21.34	FT
2	510537-06	WIRE, 14 GA., 19 STRAND, WHITE	22.34	FT
1	500125	CONNECTOR, BUTT SPLICE STA-KON #16	8	EA
TOLERANCES				
±				
NEXT ASSY				
FIRST USAGE: TRAILER				
TITLE: Airstream				
Harness, Frnt. Cir. L.T.				
SCALE: 1"=1'				
DATE: 10/02				
DRAWING NUMBER: 510907-02				
REV: C				
E				



REAR

Wire Gauge Chart	
	= 20 Ga. Wire
	= 18 Ga. Wire
	= 16 Ga. Wire
	= 14 Ga. Wire
	= 12 Ga. Wire
	= 10 Ga. Wire
	= 8 Ga. Wire


1. ALL CONNECTORS ARE WIRE SIDE VIEW.
2. ALL WIRES TO BE TEW, 105C, UL/CSA
3. ALL TERMINALS ARE INSULATED UNLESS NOTED.
4. SPOT TAPE ALL SETS

No.	Ga	Color	Function
8	12	Gray	+12V.
(A) 14	18	White	Front LH Spkr.(+)
(A) 14A	18	White/bk	Front LH Spkr.(+)
(A) 15	18	Gray	Front RH Spkr.(+)
(A) 15A	18	Gray/bk.	Front RH Spkr.(+)
150	W	White	Chassis Ground

Terminals	
	Spade .110 Female
	Bullet .180 Male
	Bullet .180 Female
	Bullet .156 Female
	Bullet .156 Male
	Butt Connector
	Ring .257 1/L
	Spade .250 Female
	Spade .250 Male
	Coax Connector

2		E10833-03		TERMINAL MALE 10-12 #2977994	2	E10833-03
1		5106835-01		CONNECTOR 2-WAY MALE, #2984083	1	E106835-01
ITEM		PART NUMBER		DESCRIPTION	QTY	UNIT
TOLERANCES ±.25"					DRAWN BY RUSS A	
NEXT ASSY					APPROVED BY	
-		PRODUCT LINE		22" Safari Sport Trl.		
Airstream Harness, Ceiling, C.S.						
SCALE	DATE	DRAWING NUMBER		REV.		
NTS	02/21/07	512241-01		C A		

LET	DATE	E.C.N.	REVISION RECORD	BY
-	2/07	E-00159	Preliminary Release	RA
A	4/07	E-00159	Production Release	RA



Wire Gauge Chart	
= 20 Ga. Wire	= 14 Ga. Wire
= 18 Ga. Wire	= 12 Ga. Wire
= 16 Ga. Wire	= 10 Ga. Wire
	= 8 Ga. Wire

FRONT

NOTE:


1. ALL CONNECTORS ARE WIRE SIDE VIEW.
2. ALL WIRES TO BE TEW, 105C, UL/CSA
3. ALL TERMINALS ARE INSULATED UNLESS NOTED.
4. SPOT TAPE ALL SETS

No.	Ga	Color	Function
2A	12	Yellow/blck	#1, #2, #3 Ceiling Lts.
5	12	Blue	#2LV.
5A	12	Blue/blck	Bath Light
65	10	Yellow	Solar Pnl. (+)
66	10	Green	Solar Pnl. (-)
150	W	White	Fluoresc. Ground

Terminals	
	Spade .110 Female
	Bullet .180 Female
	Bullet .180 Female
	Bullet .156 Female
	Bullet .156 Male
	Bullet Connector
	Ring .25" ID.
	Spade .250 Female
	Spade .250 Male
	Coax Connector

1	510834-04	TERMINAL FEMALE 10 #6088913	2	2E
2	510835-02	CONNECTOR 2-WAY, FEMALE #2973781	1	1E
3	510833-03	TERMINAL MALE 10-12 #2917794	4	4E
1	510836-01	CONNECTOR 4-WAY, MALE, #629454	1	1E
ITEM	PART NUMBER	DESCRIPTION	QTY	UNIT
TOLERANCES ± .25"	Airstream		DRAWN BY	
NEXT ASSY			RUSS A	
TITLE	PRODUCT LINE 22' Safari Sport Tr-L		APPROVED BY	
-				
Harness, Ceiling, R.S.				
SCALE	DATE	DRAWING NUMBER	REV	
NTS	2/19/07	512240-01	C	A

511871-03



REPLACES PN: 510905-07

LET DATE	E.C.N.	REVISION RECORD	BY
-	4/04	* Quote Only	RA
A	3/05	5135 2006 M.Y. Production Release	RA
B	6/05	5124-A JAPANESE NOTE UPDATE	MI
C	4/06	T-00509 MOVE CLR LT WIRE BREAK-OUT	MI

C.S.
TAIL LIGHT

2-WAY AMP PLUG
PLUG PN: 770017
FRONT PN: 770031-1
REAR PN: 770032-1
TERM: 770005-1 (20-14)

3-PIN PLUG
PETERSON MFG.
PNB431-491
TYP. 2 PLCS.
#1 = CIR. 19
#2 = CIR. 18
#3 = CIR. 150

CLEARANCE
LIGHTS

LICENSE
PLATE
LIGHT

C.S. MARKER
LIGHT

18-17

16-2
BACK UP
LIGHT

SPOT TAPE BODY

SPOT TAPE

R.S.
TAIL LIGHT

SPOT TAPE

CLEARANCE
LIGHTS

18-12

18-11

18-10

18-9

18-8

18-7

18-6

18-5

18-4

18-3

18-2

18-1

18-0

18-1

18-2

18-3

18-4

18-5

18-6

18-7

18-8

18-9

18-10

18-11

18-12

18-13

18-14

18-15

18-16

18-17

18-18

18-19

18-20

18-21

18-22

18-23

18-24

NOTE:
WIRE SHALL BE TEW, 105C, UL & CSA LISTED.
RECOMMENDED VENDOR:
QUALITRONICS
TELEPHONE: (765) 966-2039

No.	Ga.	Color	Cutting Length	USA Function
16	14	BLACK	*	BACK-UP L.T.S.
17	14	RED	*	L.F.T. TURN & STOP
18	14	GREEN	*	TAIL, CLEARANCE L.T.S.
19	14	BROWN	*	R.T. TURN & STOP
150	14	WHITE	*	GROUND

Terminals
Butt 180 Male
Butt 180 Female
Butt Connector
Ring Mixture
Spade 250 Female
Spade 250 Male

ITEM	PART NUMBER	DESCRIPTION		QTY	BY
TOLERANCES					DRAWN BY
± -		Airstream			RUSS A
NEXT ASSY					APPROVED BY
- -	FIRST USAGE	Trailers			
TITLE Harness, Tail & Cir. Light					
SCALE	N/A				
	DATE 04/26/04				
		DRAWING NUMBER			
		511871-03			
		REV. C			

- NOTE (DURING INSTALL FOR JAPANESE TRAILERS):
- 1) REMOVE TAIL LIGHT CONNECTORS THEN HARDWIRE PER DRAWING #952756 TAIL LIGHT CONNECTOR WIRE COLORS: RED=STOP/TURN, BLACK=MARKER, WHITE=GROUND
 - 2) REMOVE CAMERA CONNECTOR AND EXTEND CONNECTION TO ALLOW WIRES TO EXIT INNER SHELL ABOVE REAR WINDOW AT CENTER.
 - 3) FOR JAPANESE SCHEMATIC SEE #952803.
 - 4) REFERENCE DRAWING 952794 FOR LIGHT PLACEMENT PER CONFIGURATION.

