

## Winterization Guide

1. Open, drain, and flush the fresh, black, gray tank valves. Make sure all tanks are completely empty.
2. Run water pump a few minutes with faucets open to remove water from the pump lines.
3. Remove any water filter canisters.
4. Applying air to city water hook-up, keeping the pressure at 60 PSI.
  - A. Screw on the compressed air adaptor and hook airline onto the city water inlet.

- B. Open the following valves/faucets, one at a time in the following order:

**Note:** Make sure to drain the toilet last on the inside of trailer as it is the lowest interior point.

- Lavatory sink
- Shower hose
- Washer/dryer hookup (if present)
- Kitchen/Galley sink
- Ice Maker (if present).
- All outside faucets
- Shower Sprayer
- Toilet

**Note:** Some older washer/dryer hookups have a screen filter that must be drained.

**Note:** Hold the spray head open until air sprays out.

**Note:** You must unhook line to let the water drain.

**Note:** Push foot pedal down to open valve. If toilet is equipped with spray head, hold it open until air sprays out.

**Note:** Depending on your unit, you may have a washing machine, icemaker, or dishwasher. The lines to these appliances must be drained and blown out as well. If you have a tank flush, you must blow it out also. Refer to the owner's manual for more information on these appliances.

- C. Disconnect the air line
- D. Open the pressure relief valve then remove the hot water drain plug. Allow all the water to drain out.
- E. Reconnect the airline to blow out any remaining water in the hot water tank reinstall plug.
- F. Open all low-point drain lines to blow any remaining water out from the interior water system..
- G. Remove compressed air and compressed air adapter.

If you are confident you have successfully blown out all the water from your system you can now add antifreeze to all traps and the stool. One cup in each to fill p-trap.